## **ROLINE HDMI Extender, 8K60, 10m**

**Product No.** 14.01.3476


Designed for Profession

Manufacturer ROLINE

**Manufacturer No.** 14.01.3476

**EAN (single piece)** 7630049628878











HDMI Repeater to create a point-to-point connection to reduce costs for applications that require a single HDMI Port input and output device over long distances - with up to 7680x4320 @60Hz resolution!

- Ideal for display applications in conference rooms, classrooms & training facilities etc.
- Extend the HDMI Port signal up to 10/20 meters (depending on the resolution)
- Supports HDMI resolutions up to 8K @60Hz
- Compliant with HDCP 2.2 & DPCP
- Supports 8K 60Hz (max. length: 5m in; 5m out), 4K 60Hz (max. length: 10m in; 10m out);
- HDTV compatible
- Supports DTS-HD / Dolby truehd / DTS / dolby-ac3 / DSD Audio formats
- Plug & Play
- Power: via USB C cable (5 VDC, 2A) not included.

REMARK: Graphics card and display must support display stream compression (DSC) to use HDR 8K@30/60Hz∏

4K@120Hz and 2K@240Hz

| Technical specifications |                         |  |
|--------------------------|-------------------------|--|
| Manufacturer             | ROLINE                  |  |
| Product group            | Splitters and selectors |  |

| Product type                       | HDMI Extender                           |
|------------------------------------|---|
| Colour                             | grey                                    |
| Scope of delivery                  | HDMI Repeater, Quick Installation Guide |
| Interface                          | HDMI                                    |
| Max. distance                      | 10 m                                    |
| Video input                        | HDMI                                    |
| Video output                       | HDMI                                    |
| Max. resolution                    | 7680 x 4320 @60Hz (8K, UHD-2)           |
| Power supply output                | DC 5V; 2A                               |
| Operating temperature min.         | -15 °C                                  |
| Operating temperature max.         | 45 °C                                   |
| Height                             | 10 mm                                   |
| Width                              | 23 mm                                   |
| Depth                              | 60 mm                                   |
| Weight                             | 17 g                                    |
| Height of packaging (single piece) | 20 mm                                   |
| Width of packaging (single piece)  | 20 mm                                   |
| Depth of packaging (single piece)  | 70 mm                                   |
| Package weight (single             | 0.02 kg                                 |

piece)